

ULL-20011

Laluna 2 Indirect Post Top



55w COB
4,404 Lumens

IP65
Suitable for wet locations

IK08
Impact Resistant [Vandal Resistant]

EPA - 2.26

Weight - 40.7 lbs

POLE NOT INCLUDED

Construction

Aluminum

Less than 0.1% copper content - Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength, clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

Surge Suppression

Standard 10kv surge suppressor provided with all fixtures.

BUG Rating

B2 - U3 - G1

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

MicroPRIM Finishes

MicroPRIM is Ligman's trade marked decorative powder coating technology that permanently infuses colors, patterns, or imagery directly into the surface of luminaires and poles while providing protections that standard powder coating does not offer.

MicroPRIM finishes include nature-inspired wood grains and stone aesthetics, material-inspired finishes such as brushed metal, concrete, and carbon fiber. Solid colors in Ligman standard colors, as well as any RAL or Pantone color, Decorative patterns, custom imagery and more.

Coating and Infusion Process

Metal components are pre-treated and powder coated with a proprietary polyurethane-based coating engineered for outdoor architectural use. Decorative patterns or imagery are then permanently infused into the cured powder coat through a heat-based process, creating a durable, integrated finish.

Performance and Validation

MicroPRIM finishes are suitable for indoor and outdoor applications and meet AAMA2605 architectural coating requirements. Performance is validated through laboratory and real-world testing to ASTM standards for UV exposure, adhesion, abrasion, impact, salt spray, chemical resistance, and graffiti resistance.

All MicroPRIM finishes are backed by Ligman's 10-year warranty.

Key Performance Attributes

- Anti-graffiti resistance
- UV and weather resistance
- Scratch and abrasion resistance
- Natatorium Rated for installation in corrosive environments

Hardware

Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Optics & LED

Precise optic design provides exceptional light control and precise distribution of light.
LED CRI > 80

Lumen - Maintenance Life


L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Indirect adjustable reflector post top.
Perfect soft-edged ambient lighting and wide distributions delivered from a graceful contemporary structure.

A modern post top luminaire featuring an **adjustable optical system** for both **downward symmetrical** and **asymmetrical** light distributions. Equipped with a **high performance COB LED light engine**, the precision reflector system ensures **very low glare** while minimizing light pollution. Suitable for illuminating **entrances, footpaths, parking lots, and town centers**. Available in **2700K, 3000K, 3500K, and 4000K** with **CRI >80**.

The luminaire features a **white coated aluminum reflector** positioned above the light source. The housing is constructed from **low copper die cast aluminum** with high corrosion resistance and **utilizes 316 grade stainless steel fasteners**. A **durable silicone** rubber gasket and clear toughened glass complete the optical chamber. The housing undergoes a **chemical chromitized pretreatment** prior to powder coating, ensuring exceptional long term corrosion protection.

For **Dark Sky compliance**, please specify the Laluna 3 ULL-20002.



[Designed for use with SC76 (2.99\"/>

ULL-20011

Laluna 2 Indirect Post Top

PROJECT

DATE

QUANTITY

TYPE

NOTE

ORDERING EXAMPLE || ULL - 20011 - 55w - W30 - 02 - 120/277v - Options

ULL-20011

LAMP

55w COB
4,404 Lumens

LED COLOR

W27 - 2700K
W30 - 3000K
W35 - 3500K
W40 - 4000K

FINISH COLOR

01 - BLACK RAL 9011
02 - DARK GREY RAL 7043
03 - WHITE RAL 9003
04 - METALLIC SILVER RAL 9006
05 - MATTE SILVER RAL 9006
06 - LIGMAN BRONZE
07 - CUSTOM RAL

VOLTAGE

120/277v

ADDITIONAL OPTIONS


DIM - 0-10v Dimming

NAT - Natatorium Rated

A20176 - Single Arm Pole Clamp


A20276 - Single Arm Post Top

A20376 - Double Arm Post Top




A20176

Aluminum Arm Pole Clamp



A20276

Aluminum Single Arm



A20376

Aluminum Double Arm

More Custom Finishes Available Upon Request

Consult factory for pricing and lead times


MicroPRIM FINISHES

SW01 - OAK FINISH
SW02 - WALNUT FINISH
SW03 - PINE FINISH
DF - DOUGLAS FIR FINISH
CW - CHERRY WOOD FINISH
NW - NATIONAL WALNUT FINISH
SU01 - CONCRETE FINISH
SU02 - SOFTSCAPE FINISH
SU03 - STONE FINISH
SU04 - CORTEN FINISH
CSM - Custom Image/Pattern

MicroPRIM FINISHES

MP - MAPLE FINISH
MHG - MAHOGANY FINISH
BH - BEECH FINISH
CN - CHESTNUT FINISH
WMBL - WHITE MARBLE FINISH
MBL - MARBLE FINISH
GRNT - GRANITE FINISH
BGD - BRUSHED GOLD FINISH
BBRZ - BRUSHED BRONZE FINISH
CAMO - CAMOUFLAGE FINISH

MP01 - MicroPRIM RAL 9011 Black (Glossy)
MP02 - MicroPRIM RAL 7043 Dark Grey (Glossy)
MP03 - MicroPRIM RAL 9003 White (Glossy)
MP04 - MicroPRIM RAL 9006 Metallic Silver (Glossy)
MP05 - MicroPRIM RAL 9006 Matte Silver (Matte/Textured)
MP06 - MicroPRIM Ligman Bronze (Glossy)
MP07 - MicroPRIM Custom Color (Glossy)



MicroPRIM Finish

